

Resene Ceiling Paint

waterborne flat

Resene Ceiling Paint is recommended for use on ceilings of living rooms, bedrooms and dining rooms where a flat finish is required. A very low odour, low spatter product.

interior

Typical uses

- Fibrous plaster
- Paperfaced plasterboard
- Plaster glass
- Repaints

Vehicle type	100% acrylic
Pigmentation	Titanium dioxide
Solvent	Water
Finish	Flat
Colour	White and colours off white
Dry time (minimum)	45 minutes at 18°C
Recoat time (minimum)	2 hours
Sealer required	Yes
Theoretical coverage	10 sq. metres per litre
Dry film thickness	34 microns at 10 sq. metres per litre
Usual no. of coats	1-2 coats
Durability	Good
Thinning and clean up	Water; in hot dry conditions can be thinned with up to 5% Resene Hot Weather Additive
VOC	c. 1 gram per litre (see Resene VOC Summary)

Physical properties

Performance

Performance and limitations

1. Inhibits mould growth.
2. Flow and build properties mean that one coat is often enough to achieve complete hiding.
3. Excellent application properties with low spatter.
4. An Environmental Choice approved product.

Limitations

1. Do not apply at temperatures below 10°C or when it is liable to drop below 10°C during the drying period.
2. Not recommended for use in bathrooms, kitchens or laundries (use Resene SpaceCote Flat – see [Data Sheet D314](#)).
3. Will not penetrate chalking and powdery surfaces.

Please ensure the current Data Sheet and Safety Data Sheet are consulted prior to specification or application of Resene products. View Data Sheets online at www.resene.com/datasheets. If in doubt contact Resene.



Ceiling Paint waterborne flat

Surface preparation

Ensure surface is dry and free from dirt, dust and loose material. Oil, grease and mould must be removed prior to painting. Fly spots and nicotine stains must be removed using Resene Emulsifiable Solvent Cleaner (see [Data Sheet D804](#)) or sugar soap.

Sand old glossy surfaces to provide a key for subsequent paint coats.

New work, paperfaced plasterboard

Ensure new paperfaced plasterboard is prepared to a level of finish suitable for the specified paint finish. Resene Broadwall Surface Prep & Seal (see [Data Sheet D807](#)) or Resene Broadwall 3 in 1 (see [Data Sheet D810](#)) will be required to achieve a level 5 finish. Seal Resene Broadwall Surface Prep & Seal (see [Data Sheet D807](#)) with Resene Broadwall Waterborne Wallboard Sealer (see [Data Sheet D403](#)) or Resene Sureseal (see [Data Sheet D42](#)).

Seal bare substrates as required.

Sanding dust from old lead or chromate based paints or old building materials containing asbestos may be injurious to the health if inhaled or ingested. Seek expert advice if the presence of these materials is suspected.

Application

Stir thoroughly before use. Apply by brush, speed brush, synthetic fibre roller or spray. Apply one to two coats of Resene Ceiling Paint allowing at least two hours between coats.

Precautions

Ensure correct sealer is used.



Ceiling Paint SDS

Please ensure the current Data Sheet is consulted prior to specification or application of Resene products. View Data Sheets online at www.resene.com/datasheets. If the surface you propose to coat is not referred to by this Data Sheet, please contact Resene for clarification.

In Australia
PO Box 924, Beenleigh, Qld 4207
Call 1800 738 383, visit www.resene.com.au
or email advice@resene.com.au

Resene
the paint the professionals use

In New Zealand
PO Box 38242, Wellington Mail Centre, Lower Hutt 5045
Call 0800 RESENE (737 363), visit www.resene.co.nz
or email advice@resene.co.nz

Printed on environmentally responsible paper, which complies with the requirements of environmental management systems EMAS and ISO14001. Please recycle.